



- Complete protection against dust and liquids IP68
- Washable, sterilized in just seconds, no seams or crevices
- Resistant against most common disinfectants and detergents
- Low force and precise feedback key technology
- Rugged shock protected chassis
- Low noise typing
- Compact size, ergonomically low profile design
- Damage protected key design
- Integrated high resolution FSR sensor for cursor control
- Magnetic fixing option

Switching technology: Carbon pills on gold contact  
 Number of Keys: 105 (incl. 12 function keys)  
 Protection: IP68 (NEMA 4X)  
 Key travel: 1,25 mm  
 Actuation force: 1,2 N  
 Life: approx. 2 Mio. actuations  
 Chassis: desktop (silicone rubber surface)  
 Interface: USB  
 Power: Keyboard 20mA@5VDC - FSR 10mA@5VDC  
 Dimensions: 390 x 149 x 14 mm  
 Weight: 1 kg  
 Temperature: 0°C to +60°C  
 Humidity: up to 100%  
 Shock: 3x11 ms pulses (50g) on each of 3 axes  
 Vibration: 0,04g/Hz, 20Hz-2kHz, 3 hours  
 Certifications: CE, FCC Class15, Part B

| Part number | Product name        | Features           |
|-------------|---------------------|--------------------|
| PS00750     | K11-IND-FSR-USB-GER | USB, German Layout |
| PS00751     | K11-IND-FSR-USB-US  | USB, US Layout     |

Additional versions and modifications are available on request!

Made by ProKeys e.K.  
 Karlsbader Straße 1  
 08321 Zschorlau  
 Phone +49 (0)3771-5644 356  
 Fax +49 (0)3771-5644 357  
[www.prokeys.de](http://www.prokeys.de)  
[info@prokeys.de](mailto:info@prokeys.de)