



## SwingBoard



- Sealed keyboard in swivel-mounted aluminium chassis to be mounted on vertical surfaces
- Integrated rotation damper for soft sinking to the working position
- Washable, disinfected in just seconds, almost no seams or crevices
- Surfaces resistant against common detergents and disinfectants
- Low force and precise feedback key technology, low noise emmision
- Damage protected key design
- Integrated high resolution capacitive touchpad, use of separate mouse possible on 610mm-version
- compact size, hidden cable, wall mount support available on request
- CleanLock-function to avoid unintended inputs while cleaning
- Flexible printing option (laser etching) to realize specific layouts rapidly
- Integrated USB-Hub, integrated DVD-Burner available on request

Switching technology: Number of Keys: Protection: Key travel: Actuation force: Life: Interface: Power: Dimensions (WDH): Temperature: Humidity: Shock: Vibration: Certifications:

Carbon pills on gold contact 105 (incl. 12 function keys) IP65 (NEMA 4, 4X) 1,25 mm 1 N approx. 2 Mio. actuations USB 20mA@5VDC 410 (610) x 225 x 32 mm 0°C to +60°C up to 100% 3x11 ms pulses (50g) on each of 3 axes 0,04g/Hz, 20Hz-2kHz, 3 hours CE, FCC Class15, Part B

Ordering Information

Part number	Product name	Features
PS00680	SwingBoard 400	without mousepad
PS00681	SwingBoard 600	with mousepad
PS00682	Mounting Support Version 400	Option Mounting Support Version 400
PS00683	Mounting Support Version 600	Option Mounting Support Version 600
PS00684	DVD-Burner	Option integrated CD/DVD-Burner
Additional versions and modifications are available on request!		

Additional versions and modifications are available on request!

Made by ProKeys e.K. Karlsbader Straße 1 08321 Zschorlau *Phone* +49 (0)3771-5644 356 Fax +49 (0)3771-5644 357 www.prokeys.de info@prokeys.de

www.prokeys.de